TSD 86



1. PRODUCT AND COMPANY INFORMATION			
Product name	H+H Celcon Vertical Wall Panels		
Supplier	H+H UK Limited		
	Celcon House		
	Ightham		
	Sevenoaks		
	Kent TN15 9HZ	Technical Department:	
	Tel: 01732 886333	Tel. 01732 880580	

2. HAZARD IDENTIFICATION

Following manufacture, H+H Celcon Vertical Wall Panels are not deemed to be hazardous within the meaning of the Health and Safety at Work etc. Act 1974, nor are they chemically aggressive.

Steel Reinforcement:

ONLY suitably trained and competent persons, employing suitable cutting tools fitted with the correct blades, should carry out such cutting.

3. COMPOSITION / INFORMATION ON INGREDIENTS			
Description:	Autoclaved Aerated Concrete (Aircrete) lightly reinforced structural elements		
Application:	H+H Celcon Vertical Wall Panels are manufactured in the densities, strengths, and sizes as identified in the relevant current H+H UK Limited technical literature. All components are for use in construction (building) and should be used as recommended in the H+H UK Limited technical literature accompanying the products, or as available from the Technical Department.		
Composition:	The following materials are employed in the manufacture of these products: Silica Sand, Portland Cement, Dried Carbonates, Aluminium powder, Steel Reinforcement, Corrosion Protection and Water.		
Name	CAS No.	Classification / notes	
Silica sand	14808-60-7	Predominately Alpha Quartz	
Portland cement	65997-15-1	Contains Chromium VI	
Dried Carbonates	471-34-1		
Aluminium powder	7429-90-5		
Steel Wire			
Corrosion Protection		Bitumen and Polymers, no harmful health effects	

4. FIRST AID MEASURES

SKIN: Wash with soap and water, if irritation persists seek medical advice.

EYES: Irrigate immediately with water for at least 10 minutes. If irritation persists, seek

medical attention.

INGESTION: Do not induce vomiting. Drink plenty of water and seek medical attention.

INHALATION: If irritation of respiratory tract persists, seek medical advice.

5. FIRE FIGHTING MEASURES

Non-flammable. Use extinguishing media suitable for surrounding fire.

All fire extinguisher types are suitable for use on this product, however it may be necessary to carry out a fire risk assessment to identify other potential hazards that may arise from the use of any particular type of fire extinguisher in relation to other hazards or conditions present. If in doubt, assistance should be sought from the local Fire Service.

TSD 86



6. ACCIDENTAL RELEASE

H+H Celcon Vertical Wall Panel off-cuts can be recycled or disposed of with normal builder's waste. H+H Celcon Vertical Wall Panels dust should be either vacuum collected or dampened before physical recovery to reduce the level of dust in the air. Do not allow disposal into drains or sewers. Contaminated materials should not be used and should be safely disposed of according to local authority regulations.

Dust particles may also arise from handling packaged products and may cause irritation if allowed to enter the eyes, respiratory tract or contact with the skin. Where dust arises in the atmosphere, suitable eye, face, hand, respiratory and body protection should be employed by all persons involved in the operation, and the area ventilated so far as is reasonably practicable. Correct hygiene procedures should be followed before taking food, drink or smoking.

7. HANDLING AND STORAGE

See section 16. Construction (Design and Management) Regulations below.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace Exposure Limit (WEL): Where dust is generated, as a result of cutting, drilling or grinding

etc., the following Workplace Exposure Limits (WEL's) for

airborne dust are given in HSE Guidance Note EH40.

Total inhalable dust: WEL 10mg/m³ 8hrs TWA

Respirable dust: WEL 4mg/m³ 8 hrs TWA

Respirable silica: WEL 0.1mg/m³ 8hrs TWA

WEL – workplace exposure limit, TWA – time weighted average

Personal Protective Equipment (PPE):

Material may be rough in texture. Loose particles and dust that may arise from handling these products may cause irritation if allowed to enter the eyes or respiratory tract. Suitable personal protective equipment, e.g. safety footwear, head, eye, face, hand and respiratory protection, should be used.

Where cutting of Vertical Wall Panels is undertaken suitable eye, face, hand, respiratory and body protection should be employed by all persons involved in the operation. If cutting is undertaken by mechanical means (e.g. band say, portable cut-off saw or angle grinder etc.) the cutting equipment should comply with the relevant Statutory and Regulatory requirements and carried out only by suitable trained and competent persons.

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Solid
COLOUR: White
ODOUR: None
pH: N/A

BULK DENSITY: 460 - 750 kg/m³ approx. depending on product grade

SOLUBILITY: N/A
AUTOFLAMMABILITY: N/A
LOWER EXPLOSIVE LIMIT (LEL): N/A

TSD 86



10. STABILITY AND REACTIVITY

STABILITY: Product is chemically stable

REACTIVITY: No hazardous chemicals are known to be formed during use of this product

CONDITIONS TO AVOID: Damp conditions during storage

11. TOXICOLOGICAL INFORMATION

SKIN: Abrasive, may cause skin irritation

EYES: Abrasive, discomfort and irritation

INGESTION: Unlikely to be a problem

INHALATION: Unlikely to be a problem

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL: Overall environmental impact is regarded as insignificant.

MOBILITY: Insoluble

BIODEGRADABILITY: Not biodegradable.

13. DISPOSAL CONSIDERATIONS

Dispose of surplus material and packaging via authorised waste contractor in accordance with local authority regulations.

14. TRANSPORT INFORMATION

Treat as non-hazardous product.

UN No: None

IMO Classification: None

ADR Classification: None

IATA Classification: None

15. REGULATORY INFORMATION

Risk and Safety Phrases: None

TSD 86



16. OTHER INFORMATION

This data sheet does not constitute or serve as a substitute for the user's own assessment of the risks of using this product in the workplace. It is the purchaser's responsibility to ensure that the data given in this sheet is brought to the attention of anyone in their employ who are to handle or use this product. The advice given herein applies only when the product is used for the stated application.

CONSTRUCTION (DESIGN AND MANAGEMENT) REGULATIONS:

The following information is provided to assist clients, designers and contractors in the discharge of their respective duties under the Construction (Design and Management) Regulations 2015.

For the purposes of formulating the Health and Safety Plan or File, it should be noted that the product is described as **Autoclaved Aerated Concrete** (Aircrete).

H+H Celcon Vertical Wall Panels are delivered to site by road vehicles, for which suitable access and egress should be available. Where such access and egress are not available, deliveries will be made to the nearest available suitable location, subject to agreement with the client. H+H Celcon Vertical Wall Panel packs are delivered to site supported on pallets or bearers. H+H Celcon Vertical Wall Panels may either be supported directly on the one below it or may be spaced from the one below by bearers. All components are suitably wrapped and/or banded.

Storage: H+H Celcon Vertical Wall Panels may be stacked on suitable hard and level surfaces to a maximum height of two packs high. Care should be taken when removing delivery packaging to ensure that items do not fall or otherwise endanger persons handling or near them,

Where components are to be lifted into place by crane or hoist, the correct proprietary lifting equipment must be employed.

Where forklift trucks are employed for lifting components, the trucks must be suitable for the terrain/load and suitable pallets or bearers should be employed to prevent damage to components by direct contact with the forks or blades.

All waste packaging materials should be disposed of in accordance with local regulations.

Handling: Manual handling of structural components into their final position should be undertaken in accordance with the Manual Handling Regulations 1992.

For weights and dimensions of components, reference should be made to the H+H Celcon H+H technical literature.

All persons are reminded that a suitable and sufficient assessment of risks must be made of all tasks to be carried out in accordance with the relevant Statutory and Regulatory requirements.

Disclaimer: Every effort has been made to ensure the correctness of the information provided in this data sheet, which relates to the product described only, and which is supplied to product purchasers on the basis that we cannot guarantee its accuracy or completeness. Health and safety information provided in this data sheet is intended for general guidance only, and it is the responsibility of the user to ensure that suitable and sufficient assessment of hazards and risks posed in the employment of any products are undertaken and to comply with any duties imposed by Statutory or Regulatory requirements. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe any existing patents, nor is any warranty made, either expressed or implied.