

Standard Grade



Standard Grade
(no colour line)

Standard Grade is extremely versatile and can be used below DPC, as infill for beam and block flooring systems, as well as above the ground in the walling applications listed.



Celcon Blocks, Standard Grade are BBA certified and available in thicknesses from 75mm up to 355mm. Due to its all round performance, it is possible for 100mm Standard Block to be used throughout a build – in floors and all walls eliminating any site confusion.



Applications

- Internal and external leaf of cavity walls
- Solid walls
- Separating walls
- Partitions
- Multi storey buildings
- Foundations
- Beam and Block floors
- Flanking walls



Standard Grade

	Standard Grade
Compressive Strength	3.6N/mm ²
Thermal Conductivity	0.15 W/mK
Density	600 kg/m ³


Standard Grade

Celcon Blocks Standard Grade

Celcon Foundation Block
325 x 215mm



**Scratch Marked
Celcon Block**
440 x 215mm
and foundation
Blocks (all sizes)



**Plain Face
Celcon Block**
440 x 215mm



**Celcon Block
Coursing Unit**
215 x 65mm



**Plain Face
Celcon Plus Block**
630 x 215mm



**Plain Face
Jumbo Bloks**
630 x 250mm



**Plain Face
Multi Plates**
630 x 350mm



For further information and to check our most up-to-date product range please visit our website www.hhcelcon.co.uk or contact the following departments:

Sales

For sales enquiries or to find your local stockist please contact
Tel: 01732 886444
Fax: 01732 887013

Technical

For technical enquiries please contact
Tel: 01732 880580
Fax: 01732 887013
Email: technical.services@hhcelcon.co.uk