

# Standard Grade



Standard Grade  
(no colour line)

Standard Grade is extremely versatile and can be used below DPC, as infill for beam and block flooring systems, as well as above the ground in the walling applications listed.



Celcon Blocks, Standard Grade are BBA certified and available in thicknesses from 75mm up to 300mm. Due to its all round performance, it is possible for 100mm Standard Block to be used throughout a build – in floors and all walls eliminating any site confusion.



## Applications

- Internal and external leaf of cavity walls
- Solid walls
- Separating walls
- Partitions
- Multi storey buildings
- Foundations
- Beam and Block floors
- Flanking walls



Standard Grade

	Standard Grade
Compressive Strength	3.6N/mm <sup>2</sup>
Thermal Conductivity	0.15 W/mK
Density	600 kg/m <sup>3</sup>

# Standard Grade

## Celcon Blocks Standard Grade


**Celcon Foundation Block**  
325 x 215mm



**Scratch Marked  
Celcon Block**  
440 x 215mm  
and foundation  
Blocks (all sizes)



**Plain Face  
Celcon Block**  
440 x 215mm



**Celcon Block  
Coursing Unit**  
215 x 65mm



**Plain Face  
Celcon Plus Block**  
630 x 215mm



**Plain Face  
Jumbo Bloks**  
630 x 250mm



**Plain Face  
Multi Plates**  
630 x 350mm



For further information and to check our most up-to-date product range please visit our website [www.hhcelcon.co.uk](http://www.hhcelcon.co.uk) or contact the following departments:

### Sales

For sales enquiries or to find your local stockist please contact

Tel: 01732 886444

Fax: 01732 887013

### Technical

For technical enquiries please contact

Tel: 01732 880580

Fax: 01732 880581

Email: [technical.services@hhcelcon.co.uk](mailto:technical.services@hhcelcon.co.uk)