



Expansion joint if required. _____ Partial fill cavity insulation

Inner leaf - H+H Vertical Wall Panels.
4N/mm² compressive strength. 0.17W/mK
thermal conductivity

External Wall Face

Cavity Closer

Separating wall - H+H Vertical Wall
Panels. 4N/mm² compressive
strength.

Separating wall cavity filled with
mineral fibre insulation of 40kg/m³ or
less density

Helical ties at corners - ref
H+H UK Ltd detail VE004

Stairfix HRT wall ties - ref H+H UK
Ltd detail VED007

Drying in on Dabs

Minimum 100mm

These details have been produced for guidance only. It is the responsibility of the building designer to ensure that the details shown are compatible with the overall building design and will satisfy the relevant parts of the Building Regulations applicable before they are adopted into the project design.



H+H UK Limited
Technical Services Dept.
Celcon House
Ightham, Sevenoaks
Kent, TN15 9HZ.
Tel +44 (0)1732 880580
E-mail tsd@hnceicon.co.uk

REV.	DATE	DESCRIPTION	BY.
01.	2/3/17	Minor mods.	MAB.

TITLE
Vertical Wall Panel
Separating wall Detail

DWG No. VED008

DRAWN BY MAB CHECKED BY SJK

DATE 15/12/15 SCALE 1:10 REV.NO. 01